



# VÁLVULA DE BOLA PVC ENCOLAR

## SOCKET PVC BALL VALVE

### CONDICIONES DE TRABAJO / OPERATING CONDITIONS

- Temperatura máxima: **60°C**  
Maximum temperature: 60°C
- Presión máxima de servicio: **10 bar**  
Maximum service pressure: 10 bar



### ENCOLAR - Dimensiones (mm) / SOCKET - Dimensions (mm)

| Código<br>Code | Medida<br>Size | DIN    |        | Ø<br>D | Ø<br>d | L      | I      | H      | h     |
|----------------|----------------|--------|--------|--------|--------|--------|--------|--------|-------|
|                |                | Ød1    | Ød2    |        |        |        |        |        |       |
| AA 03 331      | DN15           | 20,25  | 19,75  | 50,50  | 15,00  | 107,00 | 63,00  | 80,00  | 24,00 |
| AA 03 332      | DN20           | 25,25  | 24,75  | 60,50  | 19,50  | 117,30 | 68,00  | 90,50  | 29,00 |
| AA 03 333      | DN25           | 32,25  | 31,75  | 68,00  | 25,00  | 103,80 | 83,00  | 101,60 | 30,50 |
| AA 03 334      | DN32           | 40,25  | 39,75  | 87,00  | 32,00  | 144,00 | 102,50 | 119,00 | 30,50 |
| AA 03 335      | DN40           | 50,30  | 49,70  | 101,00 | 38,00  | 161,00 | 121,50 | 141,00 | 38,00 |
| AA 03 336      | DN50           | 63,40  | 62,60  | 114,50 | 50,00  | 165,00 | 140,00 | 166,50 | 43,50 |
| AA 03 337      | DN65           | 75,45  | 74,55  | 138,50 | 63,00  | 254,50 | 193,50 | 205,00 | 62,00 |
| AA 03 338      | DN80           | 90,55  | 89,45  | 159,00 | 75,00  | 263,70 | 193,50 | 222,50 | 62,00 |
| AA 03 339      | DN100          | 110,40 | 109,80 | 210,00 | 100,00 | 318,00 | 250,00 | 275,00 | 68,50 |

### CONSTRUCCIÓN

- 1 - Maneta: **ABS**
- 2 - Eje: **PVC**
- 3 - Tuerca: **PVC**
- 4 - Bola: **PVC**
- 5 - Anillo de cierre: **PTFE**
- 6 - Cuerpo: **PVC**
- 7 - Junta tórica: **EPDM**
- 8 - Manguito: **PVC**

### MATERIALS

- 1 - Lever: **ABS**
- 2 - Stem: **PVC**
- 3 - Thread: **PVC**
- 4 - Ball: **PVC**
- 5 - Seats: **PTFE**
- 6 - Body: **PVC**
- 7 - O-ring: **EPDM**
- 8 - Sleeve: **PVC**

